

A step further in protecting your products...and your profits!

When you need strength

Standard Grip Sheet tie sheets are available in basic paper weights from 60g/m² to 300g/m². In some applications, this just isn't enough. ENDUPACK offers the Grip Pad for the most demanding applications.



Lightweight empty plastic bottles in plastic bags are being stacked 8 layers per pallets and 2 pallets high using Grip Pad for internal storage.

For years, Grip Pad has, and is still being re-used in this application



Heavy water bottles are stacked on a pallet using a thick chipboard Grip Pad



Heavy weight rolls are being shipped on pallets doubled stacked using a Grip Pad between the two pallets



Grip Pad is available in e-flute and chipboard construction

Grip Pad is re-usable and recyclable

Grip Pad



Top

*e-flute corrugated board
0.075" (2 mm) thick*

Middle

Chipboard
0.05" (1,3 mm) thick*

Bottom

Chipboard
0.160" (4 mm) thick*

Specifications

Grip Pad E-flute Corrugated Board Standard Stock Product

Sheet size : 47.25" X 39.4" (1200 mm X 1000 mm)
Approximate thickness: 0.075" (2 mm)
Grip Sheet non-slip coating: 100% 2 sides
Material: Recycled medium and liners
Quantity per pallet: 500 sheets

Grip Pad Chipboard* 2 sides coated

Sheet size : Up to 60" X 120" (2,3 m X 4,6 m)
Available thicknesses: 0.05" to 0.165" (1,3 mm to 4,4 mm)
Grip Sheet non-slip coating: 100% 2 sides, waterproof finish available
Material: Dry finish chipboard 100% recycled
Quantity per pallet: As per specification

Grip Pad Chipboard* 1 side coated

Sheet size: Up to 60" X 120" (2,3 m X 4,6 m)
Available thicknesses: 0.085" to 0.16" (2,2 mm to 4 mm)
Grip Sheet non-slip coating: 100% 1 side, top or bottom, waterproof finish available
Material: Dry finish chipboard 100% recycled
Quantity per pallet: As per specification

* *Chipboard versions of **Grip Pad** are made in Canada.*

Grip Pad is re-usable and recyclable



<http://www.endupack-sa.com>
frederic.demonfort@endupack.com
3, impasse des Filatures
27290 Pont-Authou, France

Tel: 011 33 23 22 02 29 7

Fax: 011 33 23 25 76 91 2